Listing of Claims:

This listing of claims reflects all claim amendments and replaces all prior versions, and listings, of claims in the application. Material to be inserted is in **bold and underline**, and material to be deleted is in **strikeout** or (if the deletion is of five or fewer consecutive characters or would be difficult to see) in double brackets [[]].

In brief, claim 1 has been amended, claims 11 and 12 has been cancelled, and new claims 13-21 have been added.

1. (Currently Amended) An automatic positioning system for a table saw including a saw blade, a fence, and a guide track, the fence being moveable along the guide track to alter the distance between the fence and the saw blade, the system comprising

a rail structure.

a carriage assembly connected to the fence configured to move back and forth along the rail structure thereby causing the fence to move along the guide track, and

at least two linkage structures for connecting the rail structure in parallel with the guide track, each linkage structure including a first sheet member configured for attachedment to the rail structure, a second sheet member configured for attachedment to the guide track of the table saw, and a fastening device for rigidly sandwiching the first and second sheet members in parallel together.

2. (original) The system of claim 1, each linkage structure further comprising a third sheet member configured for attachment to the rail structure in

sandwiched combination with the first and second sheet members.

- 3. (Original) The system of claim 2, wherein the second sheet member is sandwiched between the first and third sheet members.
- 4. (Original) The system of claim 2, each linkage structure further comprising

a fourth sheet member configured for attachment to the guide track of the saw in sandwiched combination with the first, second; and third sheet members.

- 5. (Original) The system of claim 4, wherein the second and fourth sheet members are sandwiched between the first and third sheet members.
- 6. (Original) The system of claim 1, wherein the second sheet member has a hook shaped portion configured to fit around at least a portion of a circular guide track.
- 7. (Original) The system of claim 5, wherein each of the second and fourth sheet members has a hook shaped portion configured to fit around at least a portion of a circular guide track.
- 8. (Original) The system of claim 1, wherein the rail structure has at least two T-shaped slots for receiving flange portions on bolt members connected to the first sheet member, thereby fastening the first sheet member to the rail structure.
- 9. (Original) The system of claim 5, wherein the rail structure has at least two T-shaped slots for receiving flange portions on bolt members connected to the first and third sheet members, thereby fastening the first and third sheet members to the rail structure.
- 10. (Original) The system of claim 1 wherein the first and second sheet members have one or more series of coinciding holes permitting the first and second

sheet members to be bolted together in different relative orientations by pairing different combinations of holes from the sheet members.

- 11. (Cancelled)
- 12. (Cancelled)
- 13. (New) An automatic positioning system for a table saw including a saw blade, a fence, and a guide track, the fence being moveable along the guide track to alter the distance between the fence and the saw blade, the system comprising

a rail structure,

a carriage assembly connected to the fence configured to move back and forth along the rail structure thereby causing the fence to move along the guide track,

at least two linkage structures for connecting the rail structure in parallel with the guide track, each linkage structure including a first sheet member configured for attachment to the rail structure, a second sheet member configured for attachment to the guide track of the table saw, and a fastening device for rigidly sandwiching the first and second sheet members together, and

each linkage structure further comprising a third sheet member configured for attachment to the rail structure in sandwiched combination with the first and second sheet members.

- 14. (New) The system of claim 13, wherein the second sheet member is sandwiched between the first and third sheet members.
- 15. (New) The system of claim 13, each linkage structure further comprising a fourth sheet member configured for attachment to the guide track of the saw in sandwiched combination with the first, second, and third sheet members.

- 16. (New) The system of claim 13, wherein the second and fourth sheet members are sandwiched between the first and third sheet members.
- 17. (New) The system of claim 13, wherein each of the second and fourth sheet members has a hook shaped portion configured to fit around at least a portion of a circular guide track.
- 18. (New) The system of claim 13, wherein the rail structure has at least two T-shaped slots for receiving flange portions on bolt members connected to the first and third sheet members, thereby fastening the first and third sheet members to the rail structure.
- 19. (New) The system of claim 13, wherein the second sheet member has a hook shaped portion configured to fit around at least a portion of a circular guide track.
- 20. (New) The system of claim 13, wherein the rail structure has at least two T-shaped slots for receiving flange portions on bolt members connected to the first sheet member, thereby fastening the first sheet member to the rail structure.
- 21. (New) The system of claim 1 wherein the first and second sheet members have one or more series of coinciding holes permitting the first and second sheet members to be bolted together in different relative orientations by pairing different combinations of holes from the sheet members.